

Technical Bulletin



Anderson Instrument Co.
156 Auriesville Road
Fultonville, NY 12072
1-518-922-5315
Fax 1-800-726-6733
www.andinst.com

Form AIC5021© 5/03
Revised: 2/1/08
Supersedes: 6/18/07

AUTOCLAVEABLE "MINI" SANITARY PRESSURE GAUGES



- Application:** Sanitary pressure gauge for equipment to be autoclaved
- Issue:** Small, sanitary pressure gauges for fractional size lines don't withstand repeated autoclave cycles.
- Solution:** The Anderson "EK" series gauge is now available with a "CPM" fitting for use on 1/2" thru 2" line sizes. When ordered with this connection option, the gauge will withstand repeated autoclave cycles with Rezero required ONLY after first autoclave. Accuracy changes less than $\pm 0.5\%$ of span for subsequent autoclaves.

TABLE 1 Sample Autoclave Test Data

Range	Initial Accuracy	Accuracy Change due to first Autoclave	Accuracy Change due to fourth Autoclave
0-30 psig	+/-1.0%	+/-2.7%	+/-0.3%
0-60 psig	+/-0.83%	+/-0.7%	+/-0%

How to Specify: Order any standard "EK" gauge and specify fitting code "123". Then order the CPM in-line fitting (see form AIC 3572) to match your line size directly. This combination provides a cost effective solution, minimizes hold-up volume, and withstands repeated autoclaving.

Specifications

Typical Performance

Over-Range Capability:	at least 25% of full scale
Accuracy:	± 1.5% F.S. from 10-90% of scale (pressure ranges) ± 1.5% F.S. from 10-90% of pressure range, ±2.0" Hg from 0-25" Hg (compound ranges)
Stability:	Within specified accuracy for 6 months under normal operating conditions.
Process Temperature Limits:	-3° to 121°C (25° to 250°F)
Ambient Temperature Limits:	4° to 49°C (40° to 120°F)
In-line Steam Sterilization Limits:	Up to 149°C (300°F) for 1 hour
Temperature Effect:	From 10-90% of pressure scale, less than ±1.25% F.S. per -12°C (10°F) change process or ambient temperature.
Autoclave Temperature Limit:	149°C (300°F)
Autoclave Cycle Limit:	One (1) hour max.

Construction/Finish

Diaphragm and Fitting:	Welded 316 "L" grade stainless steel, electropolished to max. R _a 8 micro-inches (0.2 microns)
Bourdon Tube/Socket:	304 stainless steel, welded
Movement:	Stainless steel
Case/Bezel:	304 stainless steel, satin finish to R _a max = 32 micro-inches
Lens/Crystal:	Polysulfone
Actuating Fill:	100% mineral oil. Meets FDA requirements (21CFR, 172.878 and 178.3620(a))

Dimensions

Case Diameter:	2.48" (63mm)
Overall Height:	3.20" (81mm)
Case Depth:	1.15" (31mm)

